

Fabricating Machinery, Inc.
6315 Toronto St.
Dallas, TX, 75212
(214) 688-0472
sales@fabmachine.com

60 TON

Our Best Value

Four Loaded Workstations
Dedicated Coper Notcher Station
Electric Stroke Control

The Edwards 60 Ton Ironworker is a robust machine featuring a dedicated Coper Notcher station, adding strength and stability to this great tool. Standard features include a Punch Assembly with Pedestal Die Table, 14" wide Flat Bar Shear, Angle Shear and Coper Notcher. Shear to 65,000 psi tensile. Punch to 80,000 psi tensile.

PUNCH 1-1/16" std. 1-9/16" opt.

Rating: 60 Tons
Max. Capacity: 1-1/16" in 9/16"A36
Stroke: 1-1/4"
Throat Depth: 8-7/8"
Open Height: 8-1/8"
Shut Height: 6-7/8"
Work Height: 36-9/16"

ANGLE SHEAR

Max. Capacity: 3" x 3" x 1/2"
4" x 4" x 3/8"
Work Height: 39-7/8"

FLAT BAR SHEAR

Max. Capacity: 3/8" x 14"
1/2" x 12"
3/4" x 4"
Max. Round: 7/8"
Max. Square: 7/8"
Work Height: 34-1/2"

COPER NOTCHER

Max. Capacity: 2-1/2" x 4" x 3/8"
Work Height: 39-1/2"

GENERAL SPECIFICATIONS

Standard Motor:	5 HP 3 Phase 208/240v 1725 RPM 14 AMP
Optional Motors:	5 HP 3 Phase 440/480v 1725 RPM 7 AMP 5 HP 3 Phase 575v 1725 RPM 7 AMP 5 HP 1 Phase 208/240v 1725 RPM 23 AMP
Hydraulic Pump:	3-1/2 GPM - 1 Stage
Valve Pressure:	2500 PSI
Reservoir:	7 Gallons
Cylinder:	2-1/2" Ram

DIMENSIONS

Height:	56-1/8"
Width:	46-1/8"
Depth:	36-1/8"
Shipping Weight:	2550 lb



CALL (800) 373-8206

WWW.EDWARDSIRONWORKERS.COM